



## State of the Art in Wind Power Forecasting

Giebel, Gregor

*Publication date:*  
2012

*Document Version*  
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

*Citation (APA):*  
Giebel, G. (Invited author). (2012). State of the Art in Wind Power Forecasting. Sound/Visual production (digital)

---

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.



# SafeWind

Wind Power Forecasting with Focus  
on Extremes

Workshop, Palais Brongniart, 31.08.12, Paris

## State of the Art in Wind Power Forecasting

**Gregor GIEBEL,**  
DTU Wind Energy.  
[grgi@dtu.dk](mailto:grgi@dtu.dk)



[www.safewind.eu](http://www.safewind.eu)

# State-of-the-Art for Wind Power



ANEMOS.plus

"Advanced Tools  
for the Management of Electricity Grids with Large-  
Scale Wind Generation".  
EU FP6 Contract N°: 038692

SafeWind



"Multi-scale data assimilation, advanced wind modelling &  
forecasting with emphasis to extreme weather situations  
for a safe large-scale wind power integration".  
EU FP7 Grant Agreement N°: 213740




## DELIVERABLE REPORT

The State of the Art in Short-Term Prediction of Wind Power  
A Literature Overview, 2nd Edition

DOCUMENT TYPE	Deliverable
DOCUMENT NAME:	aplus deliverable_D1.2_STP-SOTA_v1.1.docx

# State-of-the-Art in Short-term Prediction





# State-of-the-Art in Short-term Prediction

**111 pages**

**> 380 references**

**> 230 citations**

**On [Safewind.eu](http://Safewind.eu)**

# Weather Intelligence for Renewable Energies WIRE



## Wind Power

Challenging to predict  
Design of spinning reserves



## Solar Power

Problems with voltage regulation



## Transmission & distribution

Grid management  
Thermal rating - Outages



## Load Forecasting

Users' demands

Renewable energy supply and outage Issues are heavily influenced by weather:  
intelligent weather integration is the key factor for efficient grid management.

Therefore: **COST Action WIRE** – see [wire1002.ch](http://wire1002.ch).

Just about to be released on **wire1002.ch**:

## TOC:

- 1 Management summary
- 2 Political, economical and technical framework
- 3 Research and Development:  
the European approaches
  - 3.1 Wind Energy
  - 3.2 Solar Energy
  - 3.3 Grid management
  - 3.4 Wave Energy
- 4 National activities  
AT, BE, BH, BG, HR, CZ, DK, FI, FR, DE, GR,  
HU, IS, IL, IT, NL, NO, PL, RO, ES, CH, TU
- 5 Conclusions / Recommendations

156 pages.



**COST Action ES1002**  
**Weather Intelligence for Renewable Energies (WIRE)**


**CURRENT STATE Report**  
**August 2012**

**Contacts:**  
Dr. Alain Heimo  
Chair COST Action ES1002 "WIRE"  
Email: [alain.heim@meteoest.ch](mailto:alain.heim@meteoest.ch)  
Or  
List of authors in Chapter 8

# The Need



# Area used for 20% wind in 2030



300GW = 965TWh

100x100km  
onshore

+


122x122km  
offshore

In practice, wind farms occupy about 1% of the land surface area, so the actual land use needed for wind farms and roads, other services is in the region of a few hundred square kilometres.

Source: EWEA no fuel campaign

# Installation rates of wind power

## Growth of wind capacity installed *Germany, Spain and France*



Who needs forecasts:

- **Transmission companies** in areas with high wind penetration (*eg Energinet.dk, Tennet, 50Hertz, Red Electrica de España, CaISO, AEMO, ...*)
- **Electrical utilities** (*eg DONG Energy, Vattenfall, Acciona, Iberdrola, E.On, NUON, RWE, EnBW...*)
- Everyone trading on markets with sizeable shares of wind power

## General Behavior of System Operators (TSOs)

- Low wind (few percent ) penetration -> wind is ignored
- Medium penetration -> afraid of system impact, assumption: system operation not changed (DENA Study = 2x wind penetration possible = 35 GW or 64 % considering IC)
- Medium to high -> Considering new solutions, very active research (attending conferences etc. - UK)
- High penetration: very motivated to find new innovative solutions (Denmark)

Thinking:

We know best what our system can do because we are engineers

Thinking:

Because we are engineers we have to develop solutions for what society wants.


# Predictions HowTo



# Four timescales


- Turbine Control: very short.  
**Seconds** range (eg pitch angle)
- Power Plant Scheduling: short-term  
**Hours** range (ramp up coal fired power plant = 6-8 hours)
- Electricity Markets: short-term  
**Many hours.** NordPool: trading before 1200 for next day
- Maintenance Planning: medium-term  
Eg crane movements – lead time of **days**  
Ideally 2 weeks, or at least 5 days from Monday morning  
In DK used also for fuel consumption predictions

# Short-Term Prediction Overview




# Performance

# Atmospheric Predictability



# Phase and Level errors

- Errors can be phase (timing) or level errors







Since none were available, the ANEMOS project codified common criteria for performance measurements of short-term forecasting systems:

- Mean Error
  - Mean Absolute Error
  - Root Mean Square Error
  - $R^2$  (coefficient of determination)
  - Histogram of errors
- 
- Also, use separate training and validation datasets
  - Present the errors normalised with the installed capacity
- 
- Madsen, H., P. Pinson, G. Kariniotakis, H.Aa. Nielsen, T.S. Nielsen: *Standardizing the Performance Evaluation of Short-term Wind Power Prediction Models*. Wind Engineering **29**(6), pp. 475-489, 2005


# Typical results (1996 – now more like 10%)



# Typical results (1996 – now more like 10%)




# Typical results (1996 – now more like 10%)



# Error classification

WEProg (Jørgensen and Möhrle) have an interesting scheme:






# Forecast accuracy, historical (eg ISET)



- Forecasting got better during the last years
- Some of it piggybacks on improvements in meteorology
- Some is due to better interface to meteorological models (e.g., using 100m wind speed)
- Some is using multi-model approach

Graph shows error in E.ON control zone over the years, with references from the paper



# Smoothing of forecast errors

- Focken et al looked into the spatial smoothing of forecast errors – left is actual, right is derived model



- Therefore, predictions for a region always are better than predictions for a single wind farm
- Source: Lange, M., and U. Focken: [\*Physical Approach to Short-Term Wind Power Prediction\*](#). Berlin: Springer-Verlag, 2005

# History


# Ed McCarthy 1985-87

- Predicted for the large wind farms in California (Altamont, San Gorgonio etc)
- Was run in the summers of 1985-87
- On a HP 41CX programmable calculator



- Using meteorological observations and local upper air observations
- The program was built around a climatological study of the site and had a forecast horizon of 24 hours.
- It forecast daily average wind speeds with better skill than either persistence or climatology alone.


# Prediktor





- Applied in Eastern Denmark between 1993 and 1999
- *Similar: Previento*




Similar to Prediktor, but uses more stringent physical downscaling (incl stability) and specialised upscaling  
Operational at EWE, E.On, RWE, Vattenfall, EnBW  
University of Oldenburg / energy & meteo systems GmbH




# Overview Previento



# Wind Power Prediction Tool




- Developed at IMM/DTU
- Operational in Western DK 1994
- Operational for all of DK 1999
- Statistical non-parametric adaptive models for prediction of representative farms
- Upscaling statistically to installed capacity
- Employs data cleaning
- *Similar: Sipreólico, WPMS, MORE-CARE*



- Wind Power Management System = Nowcasting + Forecasting
- In use at E.On Netz since 2001, RWE since 6/2003, Vattenfall Europe 2004
- E.On case: 50 representative wind farms (soon more) from WMEP -> ANN upscaling = Nowcast
- DWD Lokalmodell and others provide for forecast
- Accuracy: after 7 hours purely NWP dominated (5% RMS for E.On Netz total area)

# MSEPS Power Prediction by WEPROG

- Power prediction built on the 75 member Multi-Scheme Ensemble Prediction System (MSEPS)
- Auto-adaptive approach
- Using dynamic weight of the individual ensemble members
- Applied on individual wind farms and area aggregated wind power
- The MSEPS is operated globally and forecasts for more than 90% of the world's installed capacity
- Forecasts are generated 4 times per day to 144 hours ahead



- **Sipreólico**

Developed by Uni Carlos III for Red Electrica España  
Uses combined forecasting with advanced statistical models

- **LocalPred**

More research oriented model by Martí of CENER  
Combines CFD and meso-scale modelling with Principal Component Analysis and sophisticated statistics

- **MORE-CARE**

Developed by ARMINES and RAL  
Uses Fuzzy Neural Networks  
Operational in Crete, Madeira, Azores, ...

# Marketplace for models

During the last 8 years, many commercial companies have appeared

Market place contains some 20-40 models

Notably:

3Tier, TrueWind, Windlogics, Precisionwind, Eurowind, GL GarradHassan, UK MetOffice, Kjeller Vindteknik, met.no, ...

- Usually coming from the adaptive statistical tools
- Means, they are based on the (medium term) past performance
- New topic (200x): weather dependent uncertainties / quantiles
- Original work done by:
  - Armines (MRI, NPRI)
  - Uni Oldenburg (large-scale weather situation, uncertainty modelling)
  - Bremnes (Local Quantile Regression)
  - Risø/IMM/DMI (Ensembles)
  - ... and many more groups




# Ramps and Variability

# Ramps and Variability forecasts


- Relatively new topic, on the agenda only since “chunk sizes” of wind power installations get quite large (>100 MW)
- Work by Garrad Hassan, CSIRO, Risø DTU, energy&meteo systems, Enfor and many others

# What is a ramp ?



20 % in 30 min ?


# What is a ramp ?



20 % in 1 hours ?

Source: Ulrich Focken, energy&meteo systems, DE: [Experiences with Extreme Event Warning and Ramp Forecasting for US Wind Farms](#). Talk on the 4<sup>th</sup> Workshop on Best Practice in the Use of Short-term Forecasting, Quebec, 16 October 2010


# What is a ramp ?




40 % in 2 hours ?

Source: Ulrich Focken, energy&meteo systems, DE: [Experiences with Extreme Event Warning and Ramp Forecasting for US Wind Farms](#). Talk on the 4<sup>th</sup> Workshop on Best Practice in the Use of Short-term Forecasting, Quebec, 16 October 2010


# Possible approach, energy&meteo systems



# GL Garrad Hassan Ramp Forecasting Results - individual wind farm



# Precipitation




$$R_{max}(n) = \max(R(n-9), R(n-8) \dots R(n) \dots R(n+8), R(n+9))$$



# Scenarios




# Example of WPPT point and quantile forecasts




# Scenarios

- Realistic development of the future – reflect the correctly calibrated quantiles and the observed auto correlation (on an appropriate scale).



## Correct (top) and naive (bottom) scenarios



# Types of forecasts required

Basic operation: Point forecasts

Operation which takes into account asymmetrical penalties on deviations from the bid: Quantile forecasts

Stochastic optimisation taking into account start/stop costs, heat storage, and/or 'implicit' storage by allowing the hydro power production to be changed with wind power production: Scenarios respecting correctly calibrated quantiles and auto correlation.

# Best Practice

# Best Practice in making the forecasts


- Use statistical approaches and NWP
- Get NWP input close to hub height
- Build a power curve from NWP wind speed and direction vs measured power
- Give uncertainties and/or quantiles
- Use several NWP models and/or ensembles
- Provision of forecasts as model installed at the client or as a service

- Get a model
- Get another model (NWP and / or short-term forecasting model)
- Work together with service provider / academia to continuously improve model accuracy
- Reduce error by predicting for a larger area (smoothing)
- Balance all errors together, not just wind
- Use the uncertainty / pdf
- Do forecasting on TSO level, not necessarily on wind farm / developer level
- Use intraday trading
- Use longer forecasts for maintenance planning
- Meteorological training for the operators
- Meteorological hotline for special cases
- Also in report on [powwow.risoe.dk](http://powwow.risoe.dk) (Giebel and Kariniotakis: *[Best Practice in Short-term Forecasting. A User's Guide](#)*. Project report for the POW'WOW project, 6 pages, 2009)



# Best Practice Workshop

- 5 Workshops held in Delft, Madrid, Bremen, Quebec and Aarhus
- On Best Practice in the **Use** of Short-term Forecasts
- Should evolve into something like a wind power forecast user group
- Based on the idea that research delivers far more than TSOs/utilities actually use – and that utilities have figured out how to use forecasts for themselves, so why not share this knowledge
- See details on [powwow.risoe.dk/BestPracticeWorkshop.htm](http://powwow.risoe.dk/BestPracticeWorkshop.htm) .



# SafeWind

## Wind Power Forecasting with Focus on Extremes

**Workshop - 31.08.2012**

L'Auditorium, Palais Brongniart, Paris



[www.safewind.eu](http://www.safewind.eu)

